



GarageZoneHeater

The Garage Zone heater turns your shop or garage into year-round functional workspace. The available thermostat provides set-it/forget-it reliability. Your Garage Zone heater will also operate with a remote thermostat and even a programmable thermostat – to bring your garage and your car up to a comfortable temperature before you even get out of bed.



Garage Zone Direct-Vent Heaters

With a GZ, you can work longer and more comfortably all winter long – even wash your car in January.

- Slim, attractive case takes up less than one square foot of your garage space.
- Directs heat to the floor where it's needed – not to the ceiling.
- Includes 24-Volt Wall Thermostat – also operates with most programmable and wireless thermostats.
- Quiet operation lets you hear the game while you work.
- Rated at 76 percent efficient A. F. U. E.



DVC-35 (35,000 Btu)

Cover:
DV-55 (55,000 Btu)

Easy-Installation – Wall-mount system

- One-person installation in less time than two can install a ceiling-mounted heater – saves labor cost.
- Standard 3-prong plug-in electrical connection – no electrician required to connect to household wiring.
- Includes venting with attractive residential-style vent cap, for a simple direct-vent connection to outside wall – no roof flashing to leak and create call-backs.
- Recesses neatly between standard wall studs to minimize floor space needed and avoid clearance issues with garage doors – no need to brace ceiling joists or run gas lines in the attic.
- For garage installation, heater must be elevated to keep burner 18 inches from floor.

Model	Garage
DVC-35-SPP	1-Car
DVC-35-IP	1-Car
DV-55-SPP	2 – 2 1/2 Car
DV-55-IP	2 – 2 1/2 Car

Specifications

DVC-35-SPP/DVC-35-IP

DV-55-SPP/ DV-55-IP

Color: Cabinet and Front Panels	Beige	Beige
BTU Input	35,000	55,000

Note: SPP models equipped with standing pilot. IP models equipped with electronic ignition.

Overall Dimensions

Width	14 1/8"	16"
Depth	10 3/8"	11 5/16"
Height	72 1/2"	82 3/8"
Shipping Weight, Lbs.	115	140 (Two Cartons)

Temperature Control

Electric 24-Volt Wall Thermostat Positive Off Setting	Yes	Yes
Blower Output, Cu. Ft./Min.	275	400

Accessories (State on Order)

Wireless Remote Wall Thermostat	TRW	TRW
Side Outlet Register	SOR-1	SOR-1
10" Side Outlet Kit	SOK-1	SOK-1
Vinyl Siding Vent Kit	DV-822	DV-822

Vent Tube Extension Kit (Fits wall up to 19") Please contact Empire Parts Department.

Minimum Clearance to Combustibles from:

Top (To Ceiling)	4"	4"
Each Side (To Nearest Adjacent Sidewall)	4" 18" with (SOR-1)	4" without Register 18" with (DV-603)
Bottom of Unit to Wood Floor	Zero	Zero

Gas Inlet

Type of Gas (State on Order)	Natural or LP	Natural or LP
Iron Pipe Size (N.P. T.)	1/2"	1/2"
Wall to Valve Inlet	7 3/4"	6 1/2"
Center of Heater to Center of 1/2" Inlet Elbow	N/A	3"
Floor Covering to Valve Inlet	4"	3 3/4"

Venting

Wall Depth Minimum	3/4"	4 1/2"
Wall Depth Maximum	10"	13"
Vent Opening Inside Wall Surface	7 1/2" Diameter	7 1/2" Diameter
Vent Opening Outside Wall Surface	7 1/2" Diameter	7 1/2" Diameter
Corner of Vent to Nearest Outside Corner of Building	12"	24"
Edge of Vent to Nearest Projecting Surface	6"	6"
Vent Projection from Outside Wall	6"	6"
Center of Flue to Floor Covering	59 1/4"	64 7/8"

Safety Control

Pilot and Main Burners Include Automatic Shut-off

Warranty

Combustion chamber carries a 10-year limited warranty. All other parts carry a 1-year limited warranty.

Note: Empire has a policy of constantly improving quality and performance of its appliances, therefore, materials and specifications are subject to change without notice.

Due to high temperatures, the appliance should be located out of traffic and away from furniture and draperies.


Children and adults should be alerted to the hazard of high surface temperature and should be kept away to avoid burns or clothing ignition.

Installation and repair should be done by a qualified service person.

DVC-35 and DV-55 models are design certified in accordance with American National Standards Institute Z21.86 (latest standard) and CSA.2.32 (latest standard) by the Canadian Standard Association, as Fan Type Direct Vent Wall Furnaces.



Shown: Standard Direct Vent Cap mounted on outside wall



Inshot Burners facilitate smooth operation on the DVC-35.



GarageZoneHeater



918 Freeburg Ave.
Belleville, IL 62220-2623
E-mail: info@empirecomfort.com

