



VENT FREE FIREPLACE SYSTEMS

 Monessen

WARM WELCOME

Nothing invites or delights like the dancing flames of a fire. For thousands of years fire has been the focal point of hearth and home and, like so many families before, we invite you to sit by ours and enjoy their warmth and beauty.



DFX24 with standard black trim and Cottage Clay firebrick



DFX VENT FREE SYSTEMS

The DFX vent free fireplace system from Monessen offers you the ability to install a fireplace anywhere in your home. With its Triple Play Burner System®, the DFX offers loose embers, glowing logs and lively yellow flames - adding immediate warmth and beauty to any room. Available in two sizes, 24 and 32 inch and offering 22,000 or 26,000 BTUs there is a Monessen vent free fireplace system made to suit your specific requirements. The DFX offers standard millivolt control operation and is available with either three or five log sets.



*CFX32 Chesapeake vent free fireplace system
with Dark Walnut wall cabinet and Cottage Clay
firebrick shown on cover*



DFX32C shown with optional -Honey Oak
mantel and Cottage Clay firebrick

DBX VENT FREE SYSTEMS

The DBX model is approved for bedroom use and features 10,000 BTUs, a 1-piece two log design and thermostat operation on the 24 inch size. Customize your Monessen vent free fireplace system by choosing either the standard black trim and louvers or the optional polished brass trim, louvers and the Cottage Clay firebrick.



DBX24C with optional face plate, Brass louvers and Cottage Clay firebrick



CFX32 Chesapeake vent free fireplace system with Dark Walnut wall cabinet

CHESAPEAKE VENT FREE SYSTEMS

With Monessen's Chesapeake vent free fireplace system, enjoying the warmth and beauty of a fire has never been easier. Beauty and convenience come standard with the Chesapeake which features the Triple Play Burner System[®], strikingly realistic log set, firebox, a finely crafted mantel (your choice of Dark Walnut or Unfinished), and exquisite decorative facing. Available in two sizes and up to 26,000 BTUs, the Chesapeake contains everything you need to add an efficient, elegant fireplace to your home. Enjoy even more convenience with optional remotes to operate your fireplace from the comfort of your couch. Other optional accessories include a Cottage Clay firebrick and variable forced air blower.





DFS32 with Cottage Red Firebrick, Black arched front, Brushed Pewter cabinet door frame and Black doors



DFS36 shown with standard trim and Cottage Red firebrick

DFS VENT FREE SYSTEMS

Our DFS series of vent free fireplace systems from Monessen offer a full sized fireplace in 32, 36 and 42 inch sizes that make fire the focal point of your room again. With an easy to use deluxe control panel, BTU's ranging from 26,000 – 38,000, and a wide variety of optional accessories to choose from including interior firebrick choices, decorative face options and trim finishes, the DFS vent free fireplace systems from Monessen are an elegant way to warm up any room in your home.





DFS42 shown with standard black trim and Cottage Red firebrick



DIS vent free fireplace insert

VENT FREE INSERT

The DIS vent free fireplace insert from Monessen is the perfect way to bring your existing wood burning fireplace to life again without the hassle of making a wood fire. This easy to install vent free insert will fit most standard masonry fireplaces with a minimum opening of 24 inches high and 33 inches wide. Available with standard black or optional Brass trim and louvers as well as an optional Brass face, this insert offers an impressive BTU range from 19,000 to 28,000 keeping up to 950 square feet warm and cozy.





Parlor shown in corner Dark Walnut cabinet with Black Colonial face and Cobbled Fieldstone liner



THE PARLOR VENT FREE FIREPLACE SYSTEM

The unique and versatile design of the Parlor vent free fireplace system makes it the perfect choice for just about any room in any home. Including fiber ceramic logs, multiple face and brick options and 20,000 BTUs, the Parlor offers excellent heating capacity and design flexibility as well. Standard millivolt control operation, Piezo igniter and CSA design certified, the 20" Parlor is available in both natural gas and propane models.



White cabinet with Grey Cobbled Fieldstone brick liner and Iron Age Colonial face (Cabinet available in unfinished. Painted white for photograph.)

STANDARD FEATURES FOR ALL SYSTEMS:

- New Triple Play Burner System® with exclusive triple effect technology producing a full random yellow flame, full depth ember bed and glowing logs (Does not apply to PL20)
- Flexible connector included
- No venting required for ease of installations
- Consumer friendly deluxe control panel with easy lift off access for blower installation (Does not apply to PL20)
- Fixed safety screen
- Junction box included for electrical hook up
- CSA design certified

DBX

- Thermostat control operation
- Single burner design with 10,000 BTU for bedroom applications
- Black trim and black louvers standard
- 10 1/2" overall depth

DFX

- Available in two sizes 24" and 32"
- DFX24 22,000 BTU and DFX32 26,000 BTU
- Black trim and black louvers standard
- DFX24 10 1/2" overall depth and DFX32 12" depth
- Optional firebrick and face plates available

CFX

- Comes with a unique, fully assembled fireplace package featuring a gas fireplace system, a beautifully crafted wood cabinet, and an elegant designer facing
- Cabinet available in Dark Walnut or Unfinished
- Available in 24" and 32" fireplace models
- 22,000, or 26,000 BTU models
- Millivolt control operation

DFS

- Available in three sizes 32", 36" and 42" units
- Available with 38,000 BTU natural gas and 34,000 BTU propane Gas
- Black trim and louvers standard
- DFS32 has 16" overall depth; DFS36 & DFS42 have 18" overall depth
- Optional firebrick and face options available
- Can be field converted from circulation to radiant with optional radiant panels

DIS

- Cottage Clay firebrick standard
- Minimum fireplace opening 33"W x 24"H
- Thermostatically controlled blower

PL20

- Accent light
- Ceramic fiber log set
- Millivolt control operation

Optional Accessories

| | DBX | DFX | CFX | DFS | DIS | PL20 |
|--|-----|-----|-----|-----|-----|------|
| Cottage Clay Firebrick | X | X | X | X | | |
| Cottage Red Firebrick | | | | X | | |
| BLO24TB | X | | | | | |
| BLO24T | | X* | X* | | | |
| BLOT | | X* | X* | X | | |
| Polished Brass louvers | X | X | | X | X | |
| Pewter louvers | | | | X | | |
| Black face plate | X | | | | X^ | |
| Black, Brass & Pewter curved and med trim | | | | X | | |
| Classic faces | | | | X | | |
| Manor faces | | | | X | | |
| Corner/wall cabinets | | X | | X | | X |
| Multi-functional Ambient Technologies® remote controls | | X | X | X | X | X |
| Arched Firebrick | | | | | | X |
| Parlor Faces | | | | | | X |

*DFX32 and CFX32 takes BLOT, DFX24 and CFX24 takes BLO24T
 ^DIS has choice of two sizes: 43"W x 33" H or 50"W x 36" H



Cottage Clay firebrick



Cottage Red firebrick



Pewter louvers



Brass louvers



Unfinished Cabinet



Medium Pewter trim



Medium Brass trim



Medium Black trim

Thermostat ON/OFF remote control with 3-step flame height adjustment and 3-speed blower control with receiver



Touch screen hand held ON/OFF remote



Programmable wireless wall thermostat with receiver



Variable thermostat controlled forced air blower (135 cfm)

See our Ambient Technologies® catalog for a complete line of remotes and thermostats.

Parlor Optional Accessories

- Multiple PL20 faces and brick options (one of each required)
- Wood cabinets in flush and corner configurations in two finishes (Unfinished and Dark Walnut)
- Removable screen front



Adobe arched firebrick liner and Black Classic face



Tuscany arched brick liner and Black Colonial face



Arched Grey Cobbled Fieldstone brick liner and Iron Age Colonial face

Vent Free Fireplace Systems

| | | | |
|---------------------------------------|---|---|---|
| Model | DFX24C | DFX32C | DBX24C |
| BTU / HR (Millivolt Control) | 17,000 - 22,000 NG / 17,000 - 22,000 LP | 20,000 - 26,000 NG / 20,000 - 26,000 LP | |
| BTU / HR (Thermostat Control) | | | 10,000 - 10,000 NG / 10,000 - 10,000 LP |
| Heat Efficiency | 99% | 99% | 99% |
| Dimensions (Actual) | 24 1/2"W x 26 1/2"H x 10 1/2"D | 32"W x 30"H x 12"D | 24 1/2"W x 26 1/2"H x 10 1/2"D |
| Dimensions (Framing) | 24 3/4"W x 26 3/4"H x 10 1/2"D | 32 1/2"W x 30 1/4"H x 12 1/4"D | 24 3/4"W x 26 3/4"H x 10 1/2"D |
| Viewing Area | 26 1/2"W x 26 1/2"H (700 sq. inches) | 30"W x 30"H (900 sq. inches) | 17 1/3"W x 17 1/3"H (300 sq. inches) |
| Model | CFX24 | CFX32 | |
| Gas Type | Natural or LP | Natural or LP | |
| BTU / HR (Millivolt Control) | 22,000 NG / LP | 26,000 NG / LP | |
| Thermal Efficiency | Up to 99% | Up to 99% | |
| Actual Dimensions (Including Cabinet) | 49 1/2"W x 42"H x 17"D | 58"W x 46"H x 18"D | |
| Blower | Optional | Optional | |
| Model | DFS32C | DFS36C | DFS42C |
| BTU / HR (Millivolt Control) | 26,000 - 38,000 NG / 26,000 - 34,000 LP | 26,000 - 38,000 NG / 26,000 - 34,000 LP | 26,000 - 38,000 NG / 26,000 - 34,000 LP |
| Thermal Efficiency | 99% | 99% | 99% |
| Dimensions (Actual) | 37"W x 34 1/2"H x 16"D | 41"W x 34 1/2"H x 18"D | 47"W x 34 1/2"H x 18"D |
| Dimensions (Framing) | 37 1/4"W x 35"H x 15 1/2"D | 41 1/4"W x 35"H x 17 1/2"D | 47 1/4"W x 35"H x 17 1/2"D |
| Opening Height | 21 3/4"H | 21 3/4"H | 21 3/4"H |
| Radiant or Circulating | Both | Both | Both |
| Model | DIS Insert Only | Small Face Plate | Large Face Plate |
| BTU / HR (Millivolt Control) | 19,000 - 28,000 NG / 23,000 - 28,000 LP | | |
| Thermal Efficiency | 99% | 99% | 99% |
| Dimensions (of Front) | 33"W x 26 3/4"H x 16 1/2"D | 43 1/4"W x 33"H | 50 1/4"W x 36"H |
| Dimensions (of Back) | 22 3/4"W x 23 7/8"H x 16 1/2"D* | | |
| Heating Area | 950 sq. ft. | | |
| Model | PL20NV | PL20PV | |
| Fuel Type | NG | LP | |
| BTU/HR | 20,000 | 20,000 | |
| Thermal Efficiency | up to 99% | up to 99% | |
| Dimensions (Actual) | 19 1/2"W x 31 7/8"H x 10 1/2"D | 19 1/2"W x 31 7/8"H x 10 1/2"D | |
| Dimensions (Framing) | 20"W x 32 1/8"H x 10"D | 20"W x 32 1/8"H x 10"D | |
| Fireplace Opening | 17 3/8"W x 22 1/4"H | 17 3/8"W x 22 1/4"H | |
| Heating Area (approx) | 352 sq. ft. | 352 sq. ft. | |
| Certifying Org. | CSA | CSA | |

*Note: Faceplate adds 1/2" for a total depth of 17"

For more information about MHSC and Monessen efficient and environmentally friendly products, please visit www.monessenhearth.com



A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361

www.monessenhearth.com

Your Monessen Dealer:

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.