

VENTED INSERT FIREPLACES



 Monessen

WARM WELCOME

Nothing invites or delights like the dancing flames of a fire. For thousands of years fire has been the focal point of hearth and home and, like so many families before, we invite you to sit by ours and enjoy their warmth and beauty.



ILDV30 shown with optional Iron Age Colonial surround with filigree



ILDV20 shown with Black Texture Beveled surround with louvers

REVEAL DIRECT VENT INSERT SYSTEMS

ILDV20, ILDV30 & ILDV40

It's easy to turn an old inefficient masonry fireplace into a cozy cost-effective heat source with a direct vent insert from Monessen. Our Reveal inserts are the perfect choice. With a large viewing area, up to 39,000 BTUs and a host of sensible options, the Reveal will show you just what a fireplace can do for your home. Standard features include Cottage Clay firebrick, a variable thermostat controlled forced air blower and Natural Flame™ burner with a strikingly realistic ceramic fiber log set. The control valve is conveniently located on the outside of the box for easy access and maintenance. Two styles and colors of designer facings make these units a perfect fit for any room.

IDV DIRECT VENT INSERT SYSTEMS

IDV380C

The IDV380C features standard Black filigree trim and Cottage Clay firebrick to create an upscale, custom look. With a larger viewing area of 382 square inches, BTUs up to 40,000 and a variety of optional accessories, our vented insert from Monessen is the perfect fit for your home.



IDV380C shown with optional
Black Beveled surround



IDV380C shown with optional Gold door frame

IDV380C shown with optional Brushed Pewter door frame

STANDARD FEATURES FOR ILDV20, ILDV30 & ILDV40 SURROUNDS:

- Clean face design
- Natural Flame™ burner with ceramic fiber log set
- 3" intake and 3" exhaust vent pipe connectors for chimney flex liners
- Thermostat blower (160 cfm) standard
- 18" flex line with On/Off shut-off valve
- Cottage Clay firebrick

STANDARD FEATURES FOR IDV380C:


- Seven piece ceramic fiber logs featuring a patented Natural Flame burner with random dancing flames and large ember bed
- Millivolt with on/off switch and variable flame height control in natural gas or propane gas
- Removable unitized black louver assembly for ease of installation
- Optional firebrick and faces available
- Natural or propane field convertible
- Flexible connector with On/Off shut off valve included
- Consumer friendly deluxe control panel with on/off switch
- Thermostat controlled blower
- Cottage Clay firebrick

Optional Accessories

IDV380C Trims and Surrounds



42/29 or
46/32 Black
Flat surround



42/29 or
46/32 Black
Beveled surround



Cabinet doors, door frames and filigree panels



Gold filigree panel, door frame
and fire screen doors



Brushed Pewter filigree panel,
door frame and fire screen doors

Trims available to mix and match to achieve a custom look.



ON/OFF shut-off valve with easy access
panel conveniently located on side of
the firebox for ILDV20, ILDV30 & ILDV40



Cottage Clay firebrick

Thermostat ON/OFF remote
control with 3-step flame
height adjustment and
3-speed blower control
with receiver



Touch screen
hand held
ON/OFF remote



Programmable wireless wall
thermostat with receiver

ILDV20,ILDV30 & ILDV40 Surrounds



Beveled
surround in
Black Texture
with hood
option



Beveled
surround in
Black Texture
with filigree
option



Beveled
surround in
Black Texture
with louver
option



Colonial
surround in
Iron Age with
filigree option

Colonial and Beveled surrounds offered in Iron Age and Black Texture.
Colonial surround features cast iron 4 $\frac{3}{4}$ " mantel shelf.



Arched Colonial surround with arched Wave filigree
Available in Black Texture and Iron Age for ILDV



Arched Colonial surround with arched Nantucket filigree
Available in Black Texture and Iron Age for ILDV

See our Ambient Technologies® catalog for a complete line of remotes and thermostats.

Vented Insert Fireplaces

Model	ILDV20	ILDV30	ILDV40
BTU	13,000 - 20,000 NG / 16,000 - 20,000 LP	20,500 - 30,000 NG / 23,000 - 30,000 LP	27,000 - 39,000 NG / 30,000 - 38,000 LP
FE Ratings (Cdn. Fireplace Efficiency)	67.5% NG / 73.9% LP	71.9% NG / 83.7% LP	70.8% NG / 79.8% LP
Dimensions (Actual)	30 1/4"W x 17 7/8"H x 16 5/8"D	34 3/8"W x 20 3/4"H x 17 5/8"D	37 1/2"W x 23 3/8"H x 18 3/8"D
Opening Dimensions	22 1/2"W (Front Width) x 18"H x 14"D x 15 1/8 (Rear Width)	28"W (Front Width) x 21"H x 16"D x 20" (Rear Width)	31"W (Front Width) x 23 1/2"H x 16 1/2"D x 23" (Rear Width)
Viewing Area	280 sq.in.	409 sq.in	512 sq.in
Design Certified	CSA	CSA	CSA

Model	IDV380C
BTU	20,500 - 30,500 (NG) 22,000 - 28,000 (LP)
FE Ratings (Cdn. Fireplace Efficiency)	69.6% NG / 66.2% LP
Dimensions (Actual)	30 3/16"W x 22 3/4"H x 16 5/16"D
Opening Dimensions	28"W x 21"H
Viewing Area	382 sq.in.
Design Certified	CSA

Cover image—ILDV40 shown with Black Texture Beveled surround with hood

For more information about MHSC and Monessen efficient and environmentally friendly products, please visit www.monessenhearth.com



A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361

www.monessenhearth.com

Your Monessen Dealer:

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.