

WINDSOR SERIES PLATE STEEL WOOD BURNING STOVES AND INSERTS



 Monessen

WARM WELCOME

Nothing invites or delights like the dancing flames of a fire. For thousands of years fire has been the focal point of hearth and home and, like so many families before, we invite you to sit by ours and enjoy their warmth and beauty.



WR1500L02 Plate steel wood burning stove with Black cast iron legs



WR2500X02 Plate steel wood burning insert

Add the traditional look and warmth of a stove to any room with our wide selection of wood burning stoves and inserts from Monessen. These wood burning products combine the heritage appeal of fine craftsmanship with the latest wood burning technology to ensure optimal functionality and timeless beauty.

THE WINDSOR SERIES PLATE STEEL WOOD BURNING INSERTS

Crafted with the same sturdy construction as our wood stoves, this masonry wood insert is designed for existing masonry fireplaces. Standard features include a brick-lined firebox, blower, and faceplate (44 1/8" W x 31" H) with nickel trim. Heating capacity up to 1,500 sq. ft.



WR300007 Large steel wood burning stove shown on cover

THE WINDSOR SERIES PLATE STEEL WOOD BURNING STOVES

PREMIUM STEEL – CAST STOVES

Style and performance – heavy 5/16" thick top; firebrick firebox lining, cast-iron door, air hood, ash lip, and base elements. Three sizes. All models include convenient ash drawer. All cast iron components are made in our Vermont foundry. Polished nickel handle to match today's interior finishes. Convective side panels reduce side clearances. Three sizes: Small (1,000 sq. ft): WR1000L02, Medium (1,5000 sq. ft): WR1500L02, Large (2,000 sq. ft): WR2000L02



WR27007 Medium steel wood burning stove



WR247001 Mobile home approved wood burning stove



WR244 Small steel wood burning stove

VALUE LINE OF STEEL STOVES

Durable and rich at a value price. Stylish rolled top adds durability without adding unnecessary bulk– 3/16" thick top has strength of 5/16" flat top. Cast iron doors provide a large ceramic glass viewing area. Air wash design helps maintain a clean glass. Firebrick firebox lining.

MOBILE HOME APPROVED WOOD STOVE MODEL WR247001

- Heating capacity up to 1,000 sq. ft.
- HUD approved for use in mobile homes; outside air connection
- Reduced clearance convection side panels

SMALL STEEL WOOD STOVE MODEL WR244

- Heating capacity up to 1,000 sq. ft.
- Features cast iron door with steel legs

MEDIUM STEEL WOOD STOVE MODEL WR270007

- Heating capacity up to 1,500 sq. ft.
- Features pedestal base with ash drawer

LARGE STEEL WOOD STOVE MODEL WR300007

- Heating capacity up to 2,000 sq. ft.
- Features pedestal base with ash drawer

The Windsor Series Plate Steel Wood Burning Stoves and Inserts

Model	WR247001 Flat top with pedestal Mobile home approved	WR244 Flat top with legs	WR270007 Flat top with pedestal	WR300007 Flat top with pedestal	WR1000L02 Step top with legs	WR1500L02 Step top with legs	WR2000L02 Step top with legs			
Heated Area*	up to 1,000	up to 1,000	up to 1,500	up to 2,000	up to 1,000	up to 1,500	up to 2,000			
Heat Output BTU/hr.	19,000	26,100	29,300	32,300	26,100	29,300	32,300			
Avg. Efficiency %	65.3	74.5	63.0	63.0	74.5	63.0	63.0			
EPA Emissions g/hr.	5.0	5.3	4.4	2.7	5.3	4.4	2.7			
Firebox Vol. cu. ft.	1.2	1.3	2.0	2.1	1.3	1.5	2.1			
Log Length	18"	18"	22"	20"	18"	22"	20"			
Stove Wt. lbs.	180	180	310	300	222	350	350			
Shipping Wt. lbs.	210	210	330	320	270	380	385			
Over-all Dims.	31 3/4" h 22.3/4" w 20 3/8" d	26 15/16" h 22 1/2" w 20 5/8" d	29 9/16" h 27" w 20 7/8" d	31 1/2" h 26 1/2" w 25 1/8" d	27" h 23 3/4" w 20 1/2" d	30" h 28 1/4" w 22 1/4" d	31" h 26 1/2" w 26" d			
Ash Drawer	NO	NO	YES	YES	YES	YES	YES			
Clearance to Combustibles	Top	54"	56"	54 1/2"	54"	56"	54 1/2"	54"		
	Single	Rear	10 1/2"	15"	13"	10"	12 1/2"	9"	10"	
		Wall	Sides	10 1/2"	18"	17 1/2"	15"	12"	11 1/2"	15"
		Pipe	Corner	10 1/2"	7"	11"	9"	7"	7"	9"
	Double	Rear	5"	N/A	N/A	N/A	8"	6"	10"	
		Wall	Sides	2 1/2"	N/A	N/A	N/A	8 1/2"	6"	14"
Pipe		Corner	2 1/2"	N/A	N/A	N/A	5 1/2"	4"	8"	

Model	WR2500X02							
Heat Area Sq. ft*	Heat Output BTU/hr.	Avg. Efficiency %	EPA Emissions g/hr	Firebox Vol. cu. ft.	Log Length	Product Wt. lbs.	Insert Dim.	Min. Fireplace Opening
up to 1,500	58,000	64%	4.7	1.3	20"	250	21 3/4" h 26 3/4" w 20 3/4" d	23 3/4" h 30 3/4" w 10" d Faceplate: 31" h x 44" w

See owners manual for complete dimensions and installation specifications. Units require 6" diameter flue connector.

*Note: Actual heating area will vary based on fuel, home construction and region.

For more information about MHSC and Monessen efficient and environmentally friendly products, please visit www.monessenhearth.com



A Brand of Monessen Hearth Systems Co.
149 Cleveland Drive, Paris, Kentucky 40361

www.monessenhearth.com

Your Monessen Dealer:

To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2010 Monessen Hearth Systems Co.